

T-2500HFE PRECISION TEMPERATURE FORCING SYSTEM

Temperature Range from -85°C to +225°C at 50Hz Power

Temperature Performance between 125°C and -55°C = 4 s

Compressed air or Dry Nitrogen Gas Source

(+10°C or lower dew point, oil-free source required)

CFC-Free, Single-Stage Mechanical Refrigeration for High Reliability

Advanced Temperature Control Algorithm

Microcomputer for Most System Functions

Separate Microprocessor Control of Temperature Control Functions

PCI Bus Temperature Controller

Pentium Motherboard

Harddrive

TFT Color Touch-screen Monitor for All Readout and Input Functions

3.25" Floppy Diskette for Setup and Data Archiving

IEEE-488.2 and RS-232C Interfaces for Network / Tester Communications

Graphical and Numerical Display of Temperature / Time Data

Self-Test Diagnostics

99-Step Temperature Cycling Capability

K-Type Thermocouple or T-Type Thermocouple for DUT Sensing

Memory With Battery Backup for Storing Setups and Data

Dual Heater Thermal Testhead

Heatless Air Dryer and Filter, Maintenance free for 2 years

Programmable Air Temperature Ramp Rate

Extra High Gas Flow Rates of 1,6 to 9,4 l/s over the full Temperature Range for Large Devices and Fixtures

Purge Gas Regulator and Programmable Purge Heater

Soak Timer

0.1°C Programmability and Display Resolution

Accuracy $\pm 1^\circ\text{C}$

Integrated Support Arm with Thermal Head (Vertically and Horizontally Motorized)

Standard 4,65" ID Double-Walled Glass Shroud

Set of Five Silicone Rubber Thermal Caps, All 1.00 inch Deep

1.00 inch diameter

1.25 inch X 1.37 inch

1.25 inch X 2.75 inch

1.25 inch X 3.50 inch

2.50 inch X 2.50 inch

Universal 208/230 Volt, 50/60 Hz, Single Phase, 20 Amp Power

CE Mark included

Please note:

60Hz operation increases cold performance by 5°C.

The specified Temperature Range relates to the AIR SENSOR positioned inside of the Output Nozzle or Output Hose. Using a DUT-SENSOR may decrease the Temperature Range!